

## Universal Dual-Path Internet & Cellular LTE Alarm Communicator

SKU: IPD-BAT-LTE

ipDatatel's newest device, the BAT LTE, is a dual-path Internet & Cellular (LTE) alarm communicator offering redundant alarm communications with industry-leading remote service capabilities when connected via keybus to supported Honeywell, DSC and GE/Caddx panels.

### Simple Installation - Easy Cellular LTE & Internet

Internet connection via Ethernet to a router or switch, and pre-activated Cellular LTE with easy wire terminal connection

### Verizon LTE Network

Best nationwide cellular LTE coverage

### Dual Hi-Gain Antennas

Dual antennas can increase cellular range by up to 50% compared to a single antenna

### Universal Compatibility

Works with alarm panels that support Contact ID signaling

### Event Notifications

Instant notifications via text/push, email, and computerized voice call

### Reduced Service Costs via Remote Panel Programming

Eliminate costly truck rolls via remote Virtual Keypad programming when connected via keybus to supported GE/Caddx, Honeywell and DSC panels

### Downloadable

Upload/Download with supported Honeywell and DSC panels via Compass and DSL V programs

### Remote Access On the Go

Remotely arm and disarm via smartphone, tablet and PC. Free SecureSmart™ mobile app with dealer branding and Virtual Keypad



## INTERACTIVE SERVICES

ipDatatel's SecureSmart Alarm app with virtual keypad coupled with ipDatatel's cellular and internet alarm communicators can help save time and reduce costs with remote access and on-the-go notifications.



# TECHNICAL SPECIFICATIONS

## Dual-Path Internet & Cellular Alarm Communicator

(BAT CDMA WIFI & BAT CDMA)

SKU: IPD-BAT-CDMA-WIFI & IPD-BAT-CDMA

### CDMA-WIFI

### CDMA

#### Frequency:

- Wi-Fi 802.11bg (mixed mode)
- Frequencies CDMA 1x 800 MHz/1900 MHz

#### Radio:

- Frequencies CDMA 1x 800 MHz/1900 MHz

#### Power:

- Externally provided 12v DC
- Typical Current 130 mA
- Max Current 180 mA

#### Power:

- Externally provided 12v DC
- Typical Current 130 mA
- Max Current 180 mA

#### Environmental:

- Temperature Range - 30° to +70°C (- 22° to +158°F)
- Humidity 0 to 95% non-condensing

#### Environmental:

- Temperature Range - 30° to +70° C (- 22° to +158° F)
- Humidity 0 to 95% non-condensing

#### Physical:

- Height 7.05 inches
- Width 4.45 inches
- Depth 1.5 inches

#### Physical:

- Height 7.05 inches
- Width 4.45 inches
- Depth 1.5 inches

#### Security Protocols Supported (Wi-Fi):

- WPA
- WPAII
- WEP



CDMA-WIFI  
PRODUCT INFO



CDMA  
PRODUCT INFO



CONTACT IPDATATEL SALES TODAY

**713.452.2700 Ext. 1**

866-896-2944 • Sales@ipdatatel.com

Become a registered dealer today [ipdatatel.com/newdealer](http://ipdatatel.com/newdealer)

Purchase ipDatatel's industry-leading devices at one of our partner distributor locations.

[ipdatatel.com/distributors](http://ipdatatel.com/distributors)

